



# LAYER 2 PLUS MANAGED INDUSTRIAL ETHERNET SWITCH


Product Data Sheet



Fiberroad Low Voltage PoE Switches are a game-changer in the world of networking technology. With the ability to deliver both power and data over Ethernet cables, these switches eliminate the hassle of dealing with separate power sources for devices such as IP cameras, VoIP phones, and wireless access points. This not only streamlines the networking infrastructure but also reduces clutter and complexity in installation projects. The 12-48VDC capability of Fiberroad Low Voltage PoE Switches ensures reliable performance while maintaining energy efficiency. By harnessing the power of existing Ethernet cabling, these switches pave the way for cost-effective and efficient network setups that can adapt to various technological demands. Whether it's in a commercial setting or a residential environment, Fiberroad Low Voltage PoE Switches offer a versatile solution for enhancing connectivity and productivity across different applications.

### Main Features

- 16x10/100/1000BASE-T Gigabit Ethernet RJ45
- 4x100/1000BASE-X SFP Slots
- Support IEEE 802.3 af/at Power Over Ethernet Standard
- Full gigabit L2+ management, easy to manage the network by CLI/WebGUI/NMS.
- Build up a redundant industrial network with STP/RSTP/MSTP/ERPSv2
- Port-based VLAN, IEEE 802.1Q VLAN, and GVRP to ease network planning
- Traffic Classification Based on IEEE 802.1p, COS, WRR, and Strict Mode
- SNMPv1/v2/v2c/v3 for different levels of network management
- Wide operating temperature range -40 to 75°C (-40 to 167°F)
- All-aluminum Case, Compact and Fanless Design



Engineered for reliability in the most demanding industrial environments, the Layer 2+ Plus Managed Industrial Ethernet Switch seamlessly integrates dual power input design to ensure uninterrupted connectivity. Enclosed in a rugged IP40-rated housing that can be easily mounted on DIN rails or walls, it excels in harsh settings where durability and uptime are critical. With its exceptional operating temperature range of -40 to 75°C, this switch is built to withstand extreme conditions.

Hardware Specifications	
Product	FR-7M3416P-24V
Copper Ports	16x10/100/1000BASE-T RJ45 Auto-MDI/MDI-X (Port 1-16)
Fiber Ports	4x100/1000BASE-X SFP Slots (Port 17-20)
Console	1x RJ45-to-RS232 Serial Port(115200)
Connector	1 removable 6-contact terminal blocks Pin 1/3 for Power 1, Pin 4/6 for Power 2
Alarm	One relay output for power failure, Alarm relay current carry ability: 1A@24V DC
RAM	128Mbyte
FLASH	32MByte
Reset Button	<5 sec: System Reboot; > 10 sec: Factory Default
Surge Protection	±6kV DC, ±6kV RJ45
Enclosure	IP40 aluminum case
Installation	DIN-Rail and Wall-mount
Dimension	160 x 132 x 70mm
Weight	1000g(Bare weight), 1300g(With package)
Switching	
Switch Architecture	Store-and-Forward
Switch Fabric	56Gbps/non-blocking
Forwarding Rate	29.76Mpps(64-byte packet size)
Packet Buffer Size	4 Mbits
Maximum Packet Length	10K bytes
MAC Address Table	8K entries, automatic source address learning and aging
Flow Control	IEEE 802.3x pause frame for full duplex, Back pressure for half duplex
PoE & Power Supply	
PoE Ports	Port 1 to 16 IEEE802.3 af/at
PoE Power Supply Type	End-span
Power Supply Pin	1/2(+), 3/6(-)
Max Power Per Port	30W
Total PWR /Input Voltage	90W(12VDC) 120W(24VDC) 240W(48VDC)
Power Consumption	15 Watts Max (without PoE load)
Environmental	
Operating Temperature	-40°C~75°C (-40 to 167°F)
Storage Temperature	-40°C~85°C (-40 to 185°F)
Operating Humidity	5%~95% (non-condensing)
MTBF	907,476 hours @ Telcordia SR-332 Standard
Heat Dissipation	65 BTU/h (non-PoE mode) 1054 BTU/h (with 240W PoE load)
Cooling	Passive Cooling, Fanless Design
Noise Level	0 dBA


Software Features	
Port Configuration	Port(Admin Status) disable/enable Copper Port: Auto-negotiation 10/100/1000Mbps full and half duplex mode selection Fiber Port: 100M/1000M speed selection Flow Control disable/enable Power saving(EEE) disable/enable Each port description
Port Status	Display each ports' speed duplex mode, link status, flow control status, auto negotiation status, Fiber Port Information, Port Traffic
Port Mirroring	Source Ingress/ Egress Port/ Both, Many-to-1 monitor
VLAN	Up to 4K VLAN groups, out of 4094 VLAN IDs IEEE 802.1Q tag-based VLAN IEEE 802.1AD Q-in-Q tunneling(Double VLAN) GVRP(Generic VLAN Registration Protocol)
Link Aggregation	IEEE 802.3ad LACP/Static trunk Supports 6 trunk groups with 4 ports per trunk
Spanning Tree Protocol	IEEE 802.1D Spanning Tree Protocol (STP) IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
Multicast	Dynamic/Static Multicast groups IGMP Snooping v1,2,3 Port-based IGMP Snooping Fast Leave GMP Querier
Rate Limitation	Per Port Rate Limitation Ingress: 16-1000000 kbps/Egress: 16-1000000 kbps
Ring	ITU-T G.8032 ERPS, Recovery time < 10ms
QoS	Traffic classification based, strict priority and WRR 8-level priority for switching -Port number -802.1p priority -802.1Q VLAN tag -DSCP/TOS field in IP Packet
ACL	IP-based ACL/MAC-based ACL ACL based on: -MAC Address -IP Address -Ethertype -Protocol Type -VLAN ID -DSCP -802.1p Priority
Security	Port Security Static MAC address IEEE 802.1x port-based network access control RADIUS authentication DHCP Snooping, DHCP option 82
PoE Management Functions	
PoE System Management	PoE Port status monitoring Total PoE power budget control PoE usage threshold and temperature threshold PoE port Priority PoE mode(PoE/PoE+/PoE++) PD reboot(Zero Traffic Duration)
PoE Schedule	Absolute/Periodic Mode

Software Features		
Layer 3 Functions		
IP Interfaces	Max. 8 VLAN interfaces	
Routing Table	Max.32 routing entries	
Routing	IPv4 software static routing	
Management		
Basic Management Interface	Console; Telnet; Web browser; SNMPv1/v2c	
Secure Management Interface	SSHv2, TLSv1.2, SNMPv2/v3, SNMP MIB	
System Management	Firmware Upgrade by HTTP protocol through Ethernet network Configuration upload/download through HTTP Remote syslog, System log LLDP protocol, SNTp PREVIEW NMS Alarm (Relay, Led, Temperature, Trap, Power)	

LED	State	Description
PWR (P1&P2)	ON	Power is being supplied
	OFF	Power is not being Supplied.
Link/ACT (1-20)	ON	Port connection is active
	Blinking	Data transmitted
	OFF	Port connection is not active

Regulatory & Warranty	
ISO	Manufactured in ISO-9001facility
Safety	IEC62368-1:2020+A11:2020
EMI	FCC Part 15B Class A, IEC 61000-3-2
EMS	IEC61000-4-2 ESD: Contact:±8kV, Air:±15kV IEC61000-4-5 Surge: Power: ±6kV; RJ45: ±4kV/ ±6kV(PoE)
Shock	IEC 60068-2-27
Free Fall	IEC 60068-2-32
Vibration	IEC 60068-2-6
Environmental	RoHS 2011/65/EU Annex II(EU)
Warranty	5 Years, Details See: <a href="https://fiberroad.com/warranty">https://fiberroad.com/warranty</a>

Package Contents	
Device	1 x Industrial Ethernet Switch
Cable	1 x DB9 female to RJ45
Installation Kit	1 x DIN-Rail Clip 2 x Wall-Mount Kits
Documentation	1 x Quick installation guide 1 x Warranty card 1 x Product notice

**Dimensions      Unit: mm****Accessories(Sold Separately)****Power Supply**

FR-I-60-24	DIN-rail 24 VDC power supply with 60W/0.6A, 85 to 264 VAC, or 120 to 370 VDC input, -20 to 70°C operating temperature
FR-I-120-48	DIN-rail 48-58V VDC power supply with 120W/1.2A, 85 to 264 VAC, or 120 to 370 VDC input, -20 to 70°C operating temperature
FR-I-240W-48	DIN-rail 48-55V VDC power supply with 240W/2A, 85 to 264 VAC, or 120 to 370 VDC input, -20 to 70°C operating temperature
FR-I-480W-48	DIN-rail 48-55V VDC power supply with 480W/4A, 85 to 264 VAC, or 120 to 370 VDC input, -20 to 70°C operating temperature

**SFP Optical Transceiver**

FRSX-1L311C-I	1.25Gb/s 1310nm 10km SFP, operation temperature range of -40°C-85°C(-40°F - 185°F)
FRSX-1L341C-I	1.25Gb/s 1310nm 40km SFP, operation temperature range of -40°C-85°C(-40°F - 185°F)
FRSX-1L5X1C-I	1.25Gb/s 1550nm 80/100km SFP, operation temperature range of -40°C-85°C(-40°F - 185°F)
FRSX-1L3523/5323C-I	1.25Gb/s 1310nm/1550nm 20km BiDi SFP, operation temperature range of -40°C-85°C (-40°F - 185°F)

**Armored Fiber Patch Cable / LAN Cable**

FRPC-A-LC	Armored LSZH LC UPC to LC UPC Duplex OS2 single mode 7.0mm for Outdoor Application , 1-50m
FRLC-A-CAT6	Armored Cat6 Snagless shielded(S/FTP) Ethernet Network Patch Cable, 26AWG, 1000Base-T, 0.5m – 3m

## Precautions

To avoid damage to the equipment and personal injury caused by improper use, please observe the following precautions:

- ❖ Keep the power off during installation, wear an anti-static wrist, and ensure that the anti-static wrist is in good contact with the skin to avoid potential safety hazards.
- ❖ The switch can work normally under the correct power supply. Please confirm that the power supply voltage matches the voltage indicated by the switch.
- ❖ Before powering on the switch, please make sure that the power circuit is not overloaded, so as not to affect the normal operation of the switch and even cause unnecessary damage.
- ❖ To avoid the risk of electric shock, do not open the case while the switch is working, even if it is not charged, do not open it yourself.
- ❖ Before cleaning the switch, pull out the power plug of the switch. Do not wipe with a wet cloth. Do not use liquid to clean it.
- ❖ The equipment installed in the rack is generally from bottom to top to avoid overload installation.
- ❖ Avoid placing other heavy objects on the surface of the switch to avoid accidents.

## Order Information

Model Number	10/100/1000Base-T RJ45	100/1000Base-X Port	PoE Standard	Input Voltage	Operating Temp.
FR-7M3416P-24V	16	4	Port 1-16 802.3 af/at	2xDC9-56V	-40 to +75°C

## Shipping

Model No.	FR-7M3416/A		FR-7M3416P/FR-7M3416BT	
Classification Codes	HS Code: 851762			
	HTS: 8517.62.00			
NDAA Compliant	Yes			
Individual Gross Weight	1.34kg		1.44kg	
Individual Package Dimension	215X203X93mm			
Package Quantity	10 Units			
Package Gross Weight	14.4kg		15.4kg	
Package Dimension	535x465x255mm			

The information in this document is subject to change without notice. Fiberroad Technology Co., Limited has made all effects to ensure the accuracy of the information, but all information in this document does not constitute any kind of warranty. Contact us for the most up-to-date product information

## For more information

For more information about Fiberroad Industrial Ethernet Switch series products, Visit <https://www.fiberroad.com> or contact your local account representative.